

**QUICK CHANGE DISCS
PREMIUM - A/O**

| Characteristics/Applications | Materials | Tool Selector |
|---|--|---------------|
| <ul style="list-style-type: none"> General purpose grinding and aggressive stock removal Deburring, edge breaking, surface leveling Mold and cavity grinding Weld removal in grits 36-60 Blending of pits, gouges, and surface imperfections use grits 80-150 Achieve various finish gradients with grits 180-320 | <ul style="list-style-type: none"> ● Ferrous ○ Non-Ferrous ○ Stainless ● Plastics ○ Exotics ○ Metal Matrix ● Composites | |

| SIZE | GRIT | MAX RPM | TYPE "S" PART # | TYPE "R" PART # |
|--------------------------------|--------------|---------------|-----------------|-----------------|
| 1" STD. PKG. 100 | 36 | 40,000 | 11087 | 35361 |
| | 40 | | 11088 | 42716 |
| | 50 | | 11089 | 34998 |
| | 60 | | 11090 | 11193 |
| | 80 | | 11091 | 11194 |
| | 100 | | 11092 | 38037 |
| | 120 | | 11093 | 11196 |
| | 180 | | 11095 | 11198 |
| 240 | 11096 | 11199 | | |
| 1½" STD. PKG. 100 | 36 | 25,000 | 11099 | 11202 |
| | 40 | | 11100 | 11203 |
| | 50 | | 11101 | 11204 |
| | 60 | | 11102 | 11205 |
| | 80 | | 11103 | 11206 |
| | 100 | | 11104 | 11207 |
| | 120 | | 11105 | 11208 |
| | 150 | | 11106 | 43491 |
| | 180 | | 11107 | 11210 |
| | 240 | | 11108 | 11211 |
| 320 | 11109 | 33983 | | |
| 2" STD. PKG. 100 | 24 | 25,000 | 11110 | 11213 |
| | 36 | | 11111 | 11214 |
| | 40 | | 11112 | 11215 |
| | 50 | | 11113 | 11216 |
| | 60 | | 11114 | 11217 |
| | 80 | | 11115 | 11218 |
| | 100 | | 11116 | 11219 |
| | 120 | | 11117 | 11220 |
| | 150 | | 11118 | 34463 |
| | 180 | | 11119 | 11222 |
| | 240 | | 11120 | 11223 |
| | 320 | | 11121 | 11224 |
| 3" STD. PKG. 50 | 24 | 20,000 | 11122 | 11225 |
| | 36 | | 11123 | 11226 |
| | 40 | | 11124 | 11227 |
| | 50 | | 11125 | 11228 |
| | 60 | | 11126 | 11229 |
| | 80 | | 11127 | 11230 |
| | 100 | | 11128 | 11231 |
| | 120 | | 11129 | 11232 |
| | 150 | | 11130 | 11233 |
| | 180 | | 11131 | 11234 |
| 240 | 11132 | 11235 | | |
| 320 | 11133 | 11236 | | |


4" available Type "R" & "S". Quick Change Test Kits — Page 53.

TYPE "R"




*Equal to Lockit®,
PowerLock III® &
Roloc TR®*

TYPE "S"



*Equal to SocAtt®,
PowerLock II® &
Roloc TSM®*



**QUICK CHANGE DISCS
GRINDING AID - A/O**

| Characteristics/Applications | Materials | Tool Selector |
|---|---|---------------|
| <ul style="list-style-type: none"> The supersize is designed to grind aircraft grade aluminum and high silicon metal matrix A better option for heat generating metals such as high nickel alloys Extended life on most applications | <ul style="list-style-type: none"> ● Ferrous ○ Non-Ferrous ● Plastics ○ Exotics ○ Metal Matrix ● Composites | |

| SIZE | GRIT | MAX RPM | TYPE "S" PART # | TYPE "R" PART # |
|--------------------------------|------|---------------|-----------------|-----------------|
| 1½" STD. PKG. 100 | 36 | 25,000 | 32016 | 32055 |
| | 40 | | 45149 | 38610 |
| | 50 | | 16817 | 40939 |
| | 60 | | 32015 | 32054 |
| | 80 | | 32014 | 32053 |
| | 100 | | 32013 | 32052 |
| 2" STD. PKG. 100 | 120 | 32012 | 32051 | |
| | 24 | — | — | |
| | 36 | 16827 | 32050 | |
| | 40 | 38606 | 39869 | |
| | 50 | 16829 | 32049 | |
| | 60 | 16830 | 32048 | |
| 3" STD. PKG. 50 | 80 | 16831 | 32047 | |
| | 100 | 32017 | 32046 | |
| | 120 | 16833 | 32045 | |
| | 24 | — | — | |
| | 36 | 21344 | 32044 | |
| | 40 | 40163 | 38300 | |
| 3" STD. PKG. 50 | 50 | 26668 | 32043 | |
| | 60 | 22391 | 32042 | |
| | 80 | 26825 | 32041 | |
| | 100 | 32019 | 32040 | |
| | 120 | 32018 | 32039 | |

4" available Type "R" and "S".

Holders - Page 27.

Red Part Numbers Are Stock Items
www.superiorabrasives.com

Free!
SAMPLES

Call for Details

Phone: 800-235-9123 / Fax: 800-841-3441
Quote Fax: 877-420-1952